IMPRESS-19% HIGH GLOSS HIGH SPEED FLOOR COATING

Product Description:

A highly versatile user friendly floor coating that meets today's demand for high quality and savings in labor and materials. Impress exhibits exceptionally high initial gloss with ease of application and has excellent reparability. Applause is recommended for use on all types of resilient tile, linoleum, terazzo, quarry tile or sealed wood. Apply as a standalone product for non-porous flooring or over appropriate Protegé sealer (MVP or Tuf Kote) as directed.

Features:

Produces a superior initial gloss and responds well in an aggressive high speed buffing system. Excellent resistance to dirt soil and is virtually impervious to black heel marks and scuffing. All raw materials used for production undergo a thorough quality control process before being used for manufacturing high quality products.



Specifications:

Color:

Odor:

pH:

Physical State:

Available In:

Directions:

- 1. Floor must be cleaned and free of any other floor maintenance products, either stripper or finish. If floor is old and porous, apply Tuf Kote as a sealer first according to directions. Otherwise, use MVP to seal the floor. Sealer must be dry before applying Impress finish.
- 2. With a clean mop or applicator, apply 2-3 coats of finish (wait for drying between coats).
- 3. With finish completely dry, buff with High-Speed buffer and aqua pads.

First Aid:

Storage:

